

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
24 February 2005 (24.02.2005)

PCT

(10) International Publication Number  
**WO 2005/017382 A3**

(51) International Patent Classification<sup>7</sup>: **F16D 27/08,**  
47/00

(21) International Application Number:  
PCT/US2004/024839

(22) International Filing Date: 3 August 2004 (03.08.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
60/493,594 8 August 2003 (08.08.2003) US

(71) Applicant (for all designated States except US): **AUTO-  
MOTIVE POWER SYSTEMS, LLC** [US/US]; 3199  
Lapeer Road, Auburn Hills, MI 48326 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **MOSER, George**  
[US/US]; 1450 Stillman Road, Mason, Michigan 48854

(US). **SOMMER, Gordon** [US/US]; 831 Deer Court,  
Plymouth, Michigan 48170 (US). **OSTAPOWICZ, Adam**  
[US/US]; 33229 Barrington, Westland, Michigan 48186  
(US).


(74) Agent: **OLSON, Stephen**; Harness, Dickey & Pierce,  
P.L.C., P.O. Box 828, Bloomfield Hills, MI 48303 (US).

(81) Designated States (unless otherwise indicated, for every  
kind of national protection available): AE, AG, AL, AM,  
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,  
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,  
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,  
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,  
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,  
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,  
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,  
ZW.

(84) Designated States (unless otherwise indicated, for every  
kind of regional protection available): ARIPO (BW, GH,

[Continued on next page]

(54) Title: **POWERTRAIN CLUTCH**



(57) Abstract: A powertrain clutch for transferring power from an output shaft of an engine to an input shaft of a manual transmission includes a housing and an electrically controlled clutch between the input shaft and the output shaft for selectively coupling and uncoupling the output shaft and the input shaft. The clutching arrangement further includes a clutch disposed between the input shaft and the output shaft for synchronizing a speed of the input shaft with a speed of the output shaft.

WO 2005/017382 A3



GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(88) Date of publication of the international search report:  
15 December 2005

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**Published:**

— with international search report